






宁波新三和连接电气有限公司

NINGBO NEW SANHE ELECTRIC CONTACT CO., LTD.

产品规格书
THE SPEC SHEET



Standard	UL
Rated voltage	300V
Rated current	8A
Contact resistance	20m Ω
Insulation resistance	500M Ω /DC500V
Wrth standing voltage	AC 2000V/1 Min
Standard	IEC
Rated voltage	250V
Rated current	8A
Temp.Range	-40°C~+105°C
MAX Soldering	+250°C for 5 Sec
Pitch	5.08mm
Poles	2-20p

	linear dimension							$\equiv$	—	$\square$	//	$\perp$
variable range	to 10	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	all	to 5	over 5 to 30	over 30 to 120	over 120 to
tolerance	± 0.15	± 0.25	± 0.35	± 0.45	± 0.60	± 0.75	± 0.90	0.5	0.025	0.06	0.12	0.4

产品名称 Product Name	SH222RM-3.81		
图纸比例 Drawing Scale	2:1	A4	视图 Project View
		中国宁波慈溪	
宁波新三和连接电气有限公司 NINGBO NEW SANHE ELECTRIC CONTACT CO., LTD.		TEL:+86(574)63226910 FAX:+86(574)63226900	