





宁波新三和连接电气有限公司

NINGBO NEW SANHE ELECTRIC CONTACT CO., LTD.

产品规格书
THE SPEC SHEET



Standard	UL	
Rated voltage	300V	
Rated current	8A	
Contact resistance	20m Ω	
Insulation resistance	500M Ω /DC500V	
Wrth standing voltage	AC 2000V/1 Min	
Wire range	24~16AWG	
Standard	IEC	
Rated voltage	320V	
Rated current	15A	
Wire range	1.5mm ²	
Temp.Range	-40°C~+105°C	
MAX Soldering	+250°C for 5 Sec	
Steip Length	9-10mm	
Pitch	5.0mm	
Poles	XXP	

	linear dimension							$\equiv$	—	$\square$	//	$\perp$
variable range	to 10	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	all	to 5	over 5 to 30	over 30 to 120	over 120 to
tolerance	± 0.15	± 0.25	± 0.35	± 0.45	± 0.60	± 0.75	± 0.90	0.5	0.025	0.06	0.12	0.4

产品名称 Product Name	SH335V-5.0		
图纸比例 Drawing Scale	3:1	A4	视图 Project View
		中国宁波慈溪	
宁波新三和连接电气有限公司		NINGBO NEW SANHE ELECTRIC CONTACT CO., LTD.	
		TEL: +86(574)63226910 FAX: +86(574)63226900	