







宁波新三和连接电气有限公司

NINGBO NEW SANHE ELECTRIC CONTACT CO., LTD.

产品规格书
THE SPEC SHEET



Standard	UL
Rated voltage	300V
Rated current	10A
Contact resistance	20mΩ
Insulation resistance	500MΩ/DC500V
Wrth standing voltage	AC 2000V/1 Min
Wire range	26~12AWG
Standard	IEC
Rated voltage	320V
Rated current	20A
Wire range	2.5mm ²
Temp.Range	-40°C~+105°C
MAX Soldering	+250°C for 5 Sec
Torque	0.6Nm
Steip Length	7-8mm
Pitch	5.0mm
Poles	XXp

	linear dimension							≡	—	□	//	⊥
variable range	to 10	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	all	to 5	over 5 to 30	over 30 to 120	over 120 to
tolerance	±0.15	±0.25	±0.35	±0.45	±0.60	±0.75	±0.90	0.5	0.025	0.06	0.12	0.4

产品名称 Product Name	SH136A-5.0		
图纸比例 Drawing Scale	3:1	A4	视图 Project View
中国宁波慈溪 NINGBO NEW SANHE ELECTRIC CONTACT CO., LTD.		中国宁波慈溪 TEL: +86(574)63226910 FAX: +86(574)63226900	